



5596C Series 16 Vend Price Coin-Op

Copier/Printer Cost Recovery

Accepts Visa, MasterCard, American Express Credit Cards Including Most Domestic or International Currencies & Coins And Returns Change.

*World's most powerful
16 vend price coin-op!*

FEATURES

Interfaces:

USB:

- API interface for high speed communication to host PC.
- Interfaces to Windows, Mac, Linux and other systems using virtual COM drivers.
- Works with virtually all print vending software
- Acts as slave host for interfacing to credit card based host system

RS-232 Serial Port (D-Sub):

- Sends receipt details to serial printer
- Communication with copy machines based on proprietary serial commands

10 Mb Ethernet Port:

- Web interface via username/password
- Web access designed for customization of system settings & parameters

Web access:

- Clerk/operator access to the coin-op from their desk
- Through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

- Steering Mode: 16-price capability
- Interface Mode: 16-price vend steering signal or basic 2-price.
 - Time Vend Mode: 1 second to 1000 minutes
 - Auto vend option available
 - All FDI modes allow complete control of vending signals from almost any copier/printer with an enable/copy counter signal interface

Additional Interfaces:

5813 Card Reader Interface

- Uses VendaCard formatted debit cards
- Programmable
- 2x16 LCD modules
- LCD messages configurable via web browser

Other Interface specifications:

- **Programming buttons:**
- Configure parameters and system settings
- **Bypass Mode:**
- Permits free copies or prints
- **MDB Port:**
- Communicates with MDB devices
- Selectable channels to configure MDB devices
- **ccTalk Port:**
- Communicates with ccTalk & MDB devices.
- **Keypad Port:**
- Allows for 5,000 individual PIN accounts
- Card reader service and Time Vend applications.
- **External RS-232/TTL Serial Port.**



SPECIFICATIONS

Technical Specifications

Display:	2x16 back illuminated liquid crystal
Coin Changer	CoinCo MDB Model 9302GX
Dimensions	Height: 28 inches Width: 12 inches Depth: 7.5 inches RoHS Certified
Communication Ports:	USB B Type RS-232 or RS-485 RS-485 interface is designed to support up to 255 devices on same serial network
USB Drivers	Windows XP/2000/ME/98/CE Linux, Mac OSX
Interface Cables:	Older copier/printers: TTL interface cable current copier/printers: A-B USB cable optional: Ethernet cable
Power Supply:	+5V/+12V/+24VDC 4A
Bill Acceptor	Innovative Technologies NV9
Weight	49 pounds
Temperatures	-10C—+40C
Mounting Options:	Pedestal Stand

Options

USA Technologies e-Port G6 Wireless Credit Card System

MDB CoinCo Magnum, Vortex or Guardian Coin Changer & Other Level 2/3 MDB Coin Changers.

Keypad for 5,000 PIN Access.

Pedestal Stand.

VendaCard Debit Read/Writer.

VendaKiosk Touch Screen.

MDB Innovative, CoinCo, M.E.I., APEX, ICT, MATRIX, CASHCODE,

Email us at: info@vendapin.com

Copyright © 2007 VENDAPIN LLC All rights reserved.

VENDAPIN didn't just
become #1 in the market
we invented it!

CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311



VendaKiosk 5596C Series 16 Vend Price Coin-Op

Accepts Visa, MasterCard, American Express Credit Cards Including Most Domestic or International Currencies & Coins And Returns Change.

FEATURES

Specifications:

USB:

- API high speed communications to the host PC.
- Interfaces to Windows, Mac, and Linux systems using virtual COM drivers.
- Works with virtually all print vending software
- Acts as slave host for interfacing to credit card based host system

RS-232 Serial Port (D-Sub):

- Sends receipt details to optional serial printer
- Communication with copy machines based on proprietary serial commands

10 Mb Ethernet Port:

- Web interface via username/password
- Web access designed for customization of system settings & parameters

Web access:

- Clerk/operator access to the coin-op from their desk or other remote location
- Through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

Steering Mode: 16-price capability

- Interface Mode: 16-price vend steering signal or basic 2-price.
- Time Vend Mode: 1 second to 1000 minutes
- Auto vend option available
- All FDI modes allow complete control of vending signals from the host vended machine.

Embedded Touch Screen PC:

- 12 Inch monitor
- WiFi
- USB, Ethernet & serial ports
- Windows XP Pro
- Cooling fan
- Commercial grade high impact screen
- 100~240 VAC 50-60 hz



CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311