



Copier/Printer/Fax Cost Recovery

5596SL Series Coin-op with 16 Vend Prices

Accepts Most Domestic or International Currencies & Coins With Change Capability.

*High Capacity MDB
Coin Changer &
Banknote Acceptor*

FEATURES

Interfaces:

USB:

- API interface for high speed communication to host PC.
- Interfaces to Windows, Mac, Linux and other systems using virtual COM drivers.
- Works with virtually all print vending software
- Acts as slave host for interfacing to credit card based host system and for vending scanned images to a USB Thumb Drive

RS-232 Serial Port (D-Sub):

- Sends receipt details to serial printer
- Two Way Communication with copy machines based on proprietary serial commands

10 Mb Ethernet Port:

- Web interface via username/ password
- Web access designed for customization of system settings & parameters

Web access:

- Clerk/operator access to the coin-op from their desk
- Through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

- Steering Mode: 16-price capability
- Interface Mode: 16-price vend steering signal or basic 2-price.
 - Time Vend Mode: 1 second to 1000 minutes
 - Auto vend option available
 - All FDI modes allow complete control of vending signals from almost any copier/printer with an enable/copy counter signal interface

VENDAPIN didn't just become #1 in the market we invented it!

CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311

Additional Interfaces:

Competitive Access Control Interface:

- **Programming buttons:**
 - Configure parameter settings and selection for reading meters or printing of reports.
- **Bypass Mode:**
 - Permits free copies or prints & meter readings
- **MDB Port:**
 - Communicates with MDB devices
 - Selectable channels to configure MDB devices
 - Communicates with ccTalk & MDB devices.
- **Keypad Port:**
 - Allows for 5,000 individual PIN accounts
 - Card reader service and Time Vend applications.
- **External RS-232/TTL Serial Port.**
 - Interface to Debitek, ICT, Jamex, Blackboard and virtually any on-line or stand alone access control system. Custom harness available or engineered.
- Connects to most book check out systems.



SPECIFICATIONS

Technical Specifications

Display:	2x16 back illuminated liquid crystal
Coin Changer VendaFax	Optional
Dimensions	Height: 36 inches, Width: 8 inches Depth: 7.5 inches ETL & CE Listed, RoHS Certified,
Communication Ports:	USB B Type, RS-232 or RS-485 RS-485 interface is designed to support up to 255 devices on same serial network
USB Drivers	Windows XP/2000/ME/98/CE Linux, Mac OSX
Interface Cables:	Older copier/printers: TTL interface cable current copier/printers: A-B USB cable optional: Ethernet cable
Power Supply:	+24 VDC, 6.25 amp, 5 VDC, 3.5 amp
Bill Acceptor	Optional Pyramid 5000 Series
Weight	20 pounds without coin changer or, the bill acceptor installed
Temperatures	-10C—+40C
Mounting Options:	Aluminum base plate - 12" x 12" x .124" Also can be mounted to the left/right of the copier or printer

Options

MDB CoinCo Model 9302GX, Vortex, Magnum Pro, Guardian or Pyramid CG5 Coin Changer.

Diamond Plate Polished Base Included at no additional charge

Stackerless Bill Acceptor Accepts: \$1- \$5—\$10 & \$20

Serial Cable for Interface to 3rd Party Software Programs.

USB Cable for Interface to 3rd Party Software Programs

**E-mail: sales@vendapin.com
Sales Contact: 352-796-2693
sales@vendapin.com**

<http://www.vendapin.com/index4.html>



5596SL Series Cost Recovery Copier/Printer Coin-op & Credit Card Payment Station

Accepts Most Domestic or International Currencies & Coins. Optional Bill Acceptor, Wireless Credit Card or Debit Card Payment Terminal can be added.

FEATURES

Specifications:

Compatibility:

- API high speed communications to the host PC or Copier/Printer.
- Interfaces to Windows, Mac, and Linux systems using virtual COM drivers.
- Works with virtually all Cost Recovery Print Vending Software.
- Machine interface harnesses available for virtually every copier/printer.

Dimensions:

- 30 inches height x 8 inches width x 7.5 inch depth
- Weight—20 pounds without coin changer, credit card or bill acceptor

10 Mb Ethernet Port:

- Web interface via username/password designed for customization of the system settings & parameters with real time I/O serial communications between the host machine.

Web access:

- Clerk/operator access to the coin-op from their desk or other remote location through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

Steering Mode: 16-price capability

- Interface Mode: 16-price vend steering signal or basic 2-price & Time Vend in Mode: 1 second to 1000 minutes with auto vend option available
- All FDI modes allow complete control of vending signals from the host vended machine.
- Communication with copy machines based on proprietary serial commands

Optional Mounting Features:

- Aluminum ADA compliant 12" x 12" x .124 base that slides under the copier/printer and blocks the paper cassettes from theft
- Can be bolted to the floor
- Pedestal 12" Stand with aircraft cable
- Can be bolted to the host for access
- ADA Compliant



CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311

<http://www.vendapin.com/index4.htm>