



Copier/Printer/Fax Cost Recovery

5596XL Series Coin-op with 16 Vend Prices

Accepts Optional Discover, Visa, MasterCard, American Express Credit & Debit Cards Including Most Domestic or International Currencies & Coins. Add The VendaFax VF-2 Fax Board To Send and Receive Faxes.

*High Capacity MDB
Coin Changer &
Banknote Acceptor*

FEATURES

Interfaces:

USB:

- API interface for high speed communication to host PC.
- Interfaces to Windows, Mac, Linux and other systems using virtual COM drivers.
- Works with virtually all print vending software
- Acts as slave host for interfacing to credit card based host system

RS-232 Serial Port (D-Sub):

- Sends receipt details to serial printer
- Communication with copy machines based on proprietary serial commands

10 Mb Ethernet Port:

- Web interface via username/password
- Web access designed for customization of system settings & parameters

Web access:

- Clerk/operator access to the coin-op from their desk
- Through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

Steering Mode: 16-price capability

- Interface Mode: 16-price vend steering signal or basic 2-price.
- Time Vend Mode: 1 second to 1000 minutes with 8 channels
- Auto vend option available
- All FDI modes allow complete control of vending signals from almost any copier/printer with an enable/copy counter signal interface

VENDAPIN didn't just become #1 in the market we invented it!

Additional Interfaces:

Competitive Access Control Interface:

- **Programming buttons:**
 - Configure parameters and system settings
- **Bypass Mode:**
 - Permits free copies or prints
- **MDB Port:**
 - Communicates with MDB devices
 - Selectable channels to configure MDB devices
 - Communicates with ccTalk & MDB devices.
- **Keypad Port:**
 - Allows for 5,000 individual PIN accounts
 - Card reader service and Time Vend applications.
- **External RS-232/TTL Serial Port.**
 - Interface to Debitek, ICT, Jamex, Blackboard and virtually any on-line or stand alone access control system. Custom harness available or engineered.
- **VendaFax VF-1 fax board:**
 - Allows sending and receiving faxes. Dual vend prices permitting charging one price for the 1st fax and a 2nd price for any additional pages



SPECIFICATIONS

Technical Specifications

Display:	2x16 back illuminated liquid crystal
Coin Changer & VendaFax	Optional
Dimensions	Height: 36 inches, Width: 12 inches Depth: 7.5 inches ETL & CE Listed, RoHS Certified,
Communication Ports:	USB B Type, RS-232 or RS-485 RS-485 interface is designed to support up to 255 devices on same serial network
USB Drivers	Windows XP/2000/ME/98/CE Linux, Mac OSX
Interface Cables:	Older copier/printers: TTL interface cable current copier/printers: A-B USB cable optional: Ethernet cable
Power Supply:	+24 VDC, 6.25 amp, 5 VDC, 3.5 amp
Bill Acceptor	Optional MDB
Weight	31 pounds without coin changer, bill acceptor or credit card system installed
Temperatures	-10C—+40C
Mounting Options:	Aluminum base plate - 12" x 8" x .124"

Options

MDB CoinCo Model 9302GX, Vortex, Magnum Pro, Guardian or Pyramid CG5 Coin Changer.

USA Technologies Edge e-Port Wireless Credit Card System

**Locking Coin Cash Box
VendaFax VF-2 Fax Board**

VendaCard Debit Read/Writer & RFID Contactless Debit Cards.

MDB Innovative, CoinCo, M.E.I., APEX, ICT, MATRIX, CASHCODE, GPT Bill

Email: info@vendapin.com
Sales Contact: 352-796-2693

Original Equipment Manufacturing
E-mail: sales@vendapin.com
Sales Contact: 352-796-2693

CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311

<http://www.vendapin.com/5596.htm>



DA
Co
mpl
iant

5596XL Series Cost Recovery Copier/Printer/Fax Coin-op

Accepts Optional Discover, Visa, MasterCard, American Express Credit & Debit Cards Including Most Domestic or International Currencies & Coins. Add The VendaFax VF-1 Fax Board To Send and Receive Faxes..

FEATURES

Specifications:

Compatibility:

- API high speed communications to the host PC or Copier/Printer.
- Interfaces to Windows, Mac, and Linux systems using virtual COM drivers.
- Works with virtually all Cost Recovery Print Vending Software.
- Machine interface harnesses available for virtually every copier/printer.

Dimensions:

- 36 inches height x 12 inches width x 6.25 inch depth
- Weight—31 pounds without, credit card system, coin changer or bill acceptor

10 Mb Ethernet Port:

- Web interface via username/password designed for customization of the system settings & parameters with real time I/O serial communications between the host machine.

Web access:

- Clerk/operator access to the coin-op from their desk or other remote location through a network to credit or debit for copies or prints.
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

Steering Mode: 16-price capability

- Interface Mode: 16-price vend steering signal or basic 2-price & Time Vend in Mode: 1 second to 1000 minutes with auto vend option available
- All FDI modes allow complete control of vending signals from the host vended machine.
- Communication with copy machines based on proprietary serial commands

Mounting Features:

- Aluminum ADA compliant 12" x 17.5" x .124 base that slides under the copier/printer and blocks the paper cassettes from theft
- Can be bolted to the floor
- Aircraft cable secures to the host
- Slides away from the host for access



CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311

<http://www.vendapin.com/5596.htm>