



Model CTD-105 Series CD/DVD & Envelope Dispenser

TTL, TTL Totalizer, USB, RS-232 & RS-485

FEATURES

CTD-105 Version (TTL)

P/N: 900527-CTD105 (TTL)
P/N: 900527-CTD105 (Accumulator)

VCB-1 Board Interface:

Input Signals

- Dispense
- Reset

Output Signals

- Ready
- Empty
- Stuck

Precision motor control
P.S. Input: +24VDC 1A
Programmable dip switch used for:

- Number of Retries
- Card Hold or Card Eject
- Selectable accumulation

CTD-105 Version

(Patent Pending)
P/N: 900527-CTD105 (USB)
P/N: 900527-CTD105 (RS232-485)

VCB-2 Board Interface:

- USB (Standard)
- RS-232 RJ-12 Port (TX/RX/Gnd)
- RS-485 Port (up to 255 devices)
- Dispense Test Button
- Ready/Empty/Stuck LED Header
- XT Style +5V/+12V Input Port

CTD-105 CD/DVD dispenser uses easy to understand API commands to be used for issuing the commands for dispense, empty status, ready status, and others. We provide the free CD/DVD dispenser API tester software to assist the developers to quickly integrate their card dispensers into their systems.

VENDAPIN didn't just
become #1 in the market
we invented it!

Priority #1
Quality & Customer

CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: 352.796.2693
Fax: 775.256.6311

World's most reliable!

Our most popular CTD-105 series CD/DVD & card board envelope dispenser is well-engineered for rugged reliable CD/DVD dispensing service.

Why would our CD/DVD & card board envelope dispenser be considered as the best choice for your system requirements?

- It's designed to dispense CD's & DVD's in card board or paper envelopes.
- The Adjustment Gate is designed for easy CD/DVD thickness adjustment, which can be done with a basic screw driver.
- Wide range of interface choice (TTL, USB, RS-232 or RS-485) to meet your system requirements
- Excellent easy to understand documentation on how to interface our CD/DVD dispenser into your system via; TTL, TTL Totalizer, USB, RS-232 or RS-485 Serial.



SPECIFICATIONS

Technical Specifications

Display:	Empty/Stuck/Ready LED Output Interface
Dispense Cycle	1.5-2.0 seconds
CD/DVD Dimensions	Length: 125 mm—129 mm Width: 125 mm—129 mm Thickness: 0.22 mm—3 mm Can hold up to 85-100 CD/DVD's
Communication Port:	CTD-105: USB B Type, RS-232 or RS-485 RS-485 interface is designed to support Up to 255 devices on same serial network
USB Drivers (CTD-202)	Windows XP/2000/ME/98/CE Linux, Mac OSX & 9
Interface Cable:	CTD-105 TTL: TTL interface cable CTD-105: A-B USB cable (Included) CTD-105: RS-232 RJ-12-RS-232 serial cable
Power Supply:	CTD-105 TTL: +24VDC 1A CTD-105 USB/SERIAL: +5VDC/+12VDC 1A
Dimensions:	8 x 9.5 x 20.5 cm (7 x 8 x 9 in.)
Weight	1.81 kg (4 lb)
Temperatures	-10C—+40C
Mounting options:	M3 machine screws or bottom slide bracket

Options

Card Extension Magazine

P/N:
Not Available at this time.

CTD-202/203 Power Supply Adaptor

P/N: 606012-001
U.L./CSA 100-230VAC P.S. +5VDC/+12VDC
Designed for CTD-202/203 Card Dispenser

CTD-200 Card Dispenser Tester

P/N: 900527-TEST
Designed for testing the CTD-200 card dispenser.
100-230VDC Input, +24VDC Output P.S. adaptor
is included.

Call today: 3542-796-2693 or
Email us at: sales@vendapin.com

MANUFACTURING
40 Elm Street
Dryden, NY 13053
Tel: 607.844.8134

www.VENDAPIN.com