



Copier/Printer/Fax Cost Recovery VF-2 Series Fax Board Module With Two Vend Prices

FEATURES

The VendaFax VF-2 Fax Board connects to the host fax machine or MFP copier RJ11 connector fax line output and the input of the VendaFax VF-2 RJ11 connector.

The output RJ11 cable from the VendaFax VF-2 fax board module connects to the location standard telephone RJ11 wall outlet.

The 1st fax page sent is vended at the 1st preset vend price whereas all additional fax pages sent are vended at the 2nd preset vend price.

Each fax page sent is transmitted from the VendaFax VF-2 to the Raptor II VMC board of the 5596XL/5596SL Coin-op Payment Station.

The cash value that is displayed on the 2x20 LCD is debited as each fax page is sent or as each page is printed. **Note: Not designed for fixed scanner or auto document feeders.**

VENDAPIN didn't just
become #1 in the market
we invented it!

CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311



Specifications

Power: 24V DC from copier/fax source or optional power supply. Operates most MFP Copier/Fax Machines that do not have a document feeder or fixed scanner lamp.

Dimensions: 4.75" x 2.75" x 1.38"

Shipping Weight: 0.23 kg (0.5 lb)

Environmental: 0°C to 32°C (32°F to 90°F) with 5% to 95% non-condensing humidity

Connections: (2) RJ11 jacks, (1) cable to the Coin-op 5596 series or credit card companion II Pay Station or other vending or access control device

Photo eye detection of scanned documents for positive vend signals from the moving lamp source

Monitors the phone line for a dial tone

Email: info@vendapin.com
Sales Contact: 352-796-2693

Original Equipment Manufacturing
E-mail: sales@vendapin.com
Sales Contact: 352-796-2693

<http://www.vendapin.com/vendafax.html>



5596XL Series Cost Recovery Copier/Printer/Fax Coin-op

Accepts Optional Discover, Visa, MasterCard, American Express Credit & Debit Cards Including Most Domestic or International Currencies & Coins. Add The VendaFax VF-1 Fax Board To Send and Receive Faxes..

FEATURES

Specifications:

Compatibility:

- API high speed communications to the host PC or Copier/Printer.
- Interfaces to Windows, Mac, and Linux systems using virtual COM drivers.
- Works with virtually all Cost Recovery Print Vending Software.
- Machine interface harnesses available for virtually every copier/printer.

Dimensions:

- 36 inches height x 12 inches width x 6.25 inch depth
- Weight—31 pounds without, credit card system, coin changer or bill acceptor

10 Mb Ethernet Port:

- Web interface via username/password designed for customization of the system settings & parameters with real time I/O serial communications between the host machine.

Web access:

- Clerk/operator access to the coin-op from their desk or other remote location through a network
- Network API commands (plain or encrypted) provided for full customization of system settings & parameters

FDI (Foreign Device Interface):

Steering Mode: 16-price capability

- Interface Mode: 16-price vend steering signal or basic 2-price & Time Vend in Mode: 1 second to 1000 minutes with auto vend option available
- All FDI modes allow complete control of vending signals from the host vended machine.
- Communication with copy machines based on proprietary serial commands

Mounting Features:

- Aluminum ADA compliant 12" x 17.5" x .124 base that slides under the copier/printer and blocks the paper cassettes from theft
- Can be bolted to the floor
- Aircraft cable secures to the host
- Slides away from the host for access
- ADA Compliant



CORPORATE OFFICE
16381 Cherokee Road
Brooksville, FL 34601-4202
Tel: [1] 352.796.2693
Fax: [1] 775.256.6311

<http://www.vendapin.com/5596.htm>