



Datatron III Controller

Model 5882 Keypad Access or Model 5881 Magnetic Stripe Card Reader

Datatron III Controller for access control and tracking of copiers ... or virtually any product or operation.

Effective July 1, 2004 all of VENDAPIN's Datatron III access control devices will support up to 2000 users with magneic stripe PIN cards or users with the PIN keypad.

We represent:

- Reliable solutions
- Product longevity
- Future proof products
- Low cost of ownership
- Technical service second to none

Secure

A lost Datatron Card can be invalidated and replaced by a higher level VendaCard. In the meantime, the card's original total count remains unchanged. A lost card can be deleted via the control card with keypad. Data in the controller will not be lost due to power failure.

User friendly

The total copy count of each user card can be checked via the LCD of the Datatron III Controller. The report can also be printed out to an optional serial printer. The card can also be used as an ID card. (The card is compatible with an access control system and time attendance.)

Universal

This controller operates with any make, model or type of vending machine that has both a counter signal output and an interlock switch (or an on/off switch).

Programmable pricing

Two-price capability for two products is a standard feature. The counter increments for two different products or cycles. The VendaCards are programmable from 0.01-99.99 via a control card. The maximum number of vends or counts for each card can be set up to six digits (999999).

Useful data

The total counting audit made with the Datatron III count can be checked via a management control card. ASCII data files can be exported from the Datatron II for import into your favorite Windows database program.



Call today:
352-796-2693
 or email us at:
sales@vendapin.com

VENDAPIN didn't just *become*
 #1 in the market — we
invented it!

SPECIFICATION

Technical Specification

Enclosure:	???
Display:	2-line, 32-character LED
Keypad:	4x4 flat-membrane keypad
Power requirements:	DC5V 1A or AC220V (110V) to DC5V 1A Adapter
Reader:	Magnetic card reader
Dimensions:	180 mm x 102 mm x 62.5 mm (7.08 in x 4.01 in x 2.46 in)
Weight:	1.76 lbs
:	:
:	:
:	:

Model Configurations

- **Model 5881**
 (#945881-002)
 Card version with 2000 PIN accounts and management set of cards
- **Model 5882**
 (#945882-002)
 Keypad version with 2000 PIN accounts
- **Printer**
 Optional serial printer prints reports

CORPORATE OFFICES
 16381 Cherokee Rd.
 Brooksville, FL 34601-4202
 Tel: 352.796.2693
 Fax: 775.256.6311

MANUFACTURING
 40 Elm St.
 Dryden, NY 13053
 Tel: 607.844.8134
 Fax: 775.514.7530

www.vendapin.com